

# Life Cycle Assessment of a Lithium-Ion Battery Vehicle Pack

Linda Ager-Wick Ellingsen, Guillaume Majeau-Bettez, Bhawna Singh, Akhilesh Kumar Srivastava, Lars Ole Valøen, and Anders Hammer Strømman

## Keywords:

climate change  
electric vehicles  
environmental impact assessment  
industrial ecology  
lithium-ion battery  
transportation



Supporting information is available on the JIE Web site

## Summary

Electric vehicles (EVs) have no tailpipe emissions, but the production of their batteries leads to environmental burdens. In order to avoid problem shifting, a life cycle perspective should be applied in the environmental assessment of traction batteries. The aim of this study was to provide a transparent inventory for a lithium-ion nickel-cobalt-manganese traction battery based on primary data and to report its cradle-to-gate impacts. The study was carried out as a process-based attributional life cycle assessment. The environmental impacts were analyzed using midpoint indicators. The global warming potential of the 26.6 kilowatt-hour (kWh), 253-kilogram battery pack was found to be 4.6 tonnes of carbon dioxide equivalents. Regardless of impact category, the production impacts of the battery were caused mainly by the production chains of battery cell manufacture, positive electrode paste, and negative current collector. The robustness of the study was tested through sensitivity analysis, and results were compared with preceding studies. Sensitivity analysis indicated that the most effective approach to reducing climate change emissions would be to produce the battery cells with electricity from a cleaner energy mix. On a per-kWh basis, cradle-to-gate greenhouse gas emissions of the battery were within the range of those reported in preceding studies. Contribution and structural path analysis allowed for identification of the most impact-intensive processes and value chains. This article provides an inventory based mainly on primary data, which can easily be adapted to subsequent EV studies, and offers an improved understanding of environmental burdens pertaining to lithium-ion traction batteries.

## Introduction

In the hope of mitigating climate change, both national and international goals have been set to reduce anthropogenic greenhouse gas (GHGs) emissions. Reaching these goals is made difficult by our dependence on the combustion of fossil fuels, a primary source of GHG emissions. Globally, light-duty vehicles are responsible for approximately 10% of energy use and GHG emissions (Solomon et al. 2007). A study commissioned by the World Business Council for Sustainable Development

(2004) estimates that the number of light-duty vehicles in operation will rise from roughly 750 million currently to 2 billion by 2050. This projection entails a dramatic increase in demand for gasoline and diesel supplies, which raises concerns of energy security as well as implications for climate change and urban air quality. As a result, policy makers, advocacy groups, and the automobile industry have promoted novel car technologies, such as electric vehicles (EVs), which, depending on the electricity mix used for charging, have the potential to reduce GHG

**Address correspondence to:** Linda Ager-Wick Ellingsen, Department of Energy and Process Engineering, Norwegian University of Science and Technology, E1-Høgskoleringen 5, Trondheim 7491, Norway. Email: linda.a.ellingsen@ntnu.no

© 2013 by Yale University  
DOI: 10.1111/jiec.12072

Editor managing review: Ronald Williams

Volume 18, Number 1

emissions, compared to internal combustion engine vehicles (ICEVs) (Hawkins et al. 2013; Samaras and Meisterling 2008).

The term *electric vehicle* covers several different types of vehicles: hybrid electric vehicles (HEVs); plug-in hybrid electric vehicles (PHEVs); and purely battery-driven electric vehicles (BEVs). Batteries used in PHEVs and BEVs are referred to as traction batteries. Advances in battery technology have made lithium-ion (Li-ion) the preferred option of traction batteries. There are various types of Li-ion batteries, using different compositions of cathode materials, such as  $\text{LiMn}_2\text{O}_4$  (LMO),  $\text{LiFePO}_4$  (LFP),  $\text{Li}(\text{NiCoAl})\text{O}_2$ , and  $\text{Li}(\text{Ni}_x\text{Co}_y\text{Mn}_z)\text{O}_2$  (NCM), where  $x$ ,  $y$ , and  $z$  denote different possible ratios. In connection with these cathode materials, graphite is a commonly used anode material (Cameán et al. 2010; Park et al. 2013).

EVs are, on occasion, promoted as “zero-emission” vehicles, but studies have shown that the environmental contributions of battery production and use phase can be significant (Hawkins et al. 2013; Samaras and Meisterling 2008). EVs have no tailpipe emissions, but in order to avoid problem shifting, a life cycle perspective should be applied in the environmental assessment of their traction batteries. Because limited accessibility to battery industry data makes it difficult to openly evaluate the impacts of EVs, open inventory studies on traction batteries are mostly based on secondary data. The most complete life cycle inventories (LCIs) are provided by Notter and colleagues (2010), Zackrisson and colleagues (2010), and Majeau-Bettez and colleagues (2011). The U.S. Environmental Protection Agency (USEPA) (2013) compiled inventories based on both primary and secondary data, but in order to protect the confidentiality of their primary data, they aggregated these data and complete inventories have not been provided. For their batteries, Dunn and colleagues (2012b) included a thorough investigation of the impact of recycling, but like the USEPA (2013), do not provide a complete inventory. Bauer (2010), on behalf of the Paul Scherrer Institut, performed a study commissioned by Volkswagen. The inventory is partly based on primary data, but data have been aggregated and the report is only available in German. In total, the existing literature varies with respect to the importance of impacts associated with Li-ion traction batteries, but, more important, there is a low degree of transparency.

So far, the most complete traction battery inventories are based on secondary data and do not converge to a consistent conclusion regarding the impacts pertaining to traction batteries. In order to obtain constructive insight into the environmental footprint of these components, an inventory based mostly on primary, rather than secondary, data has been compiled. This provides the opportunity for impact assessment of traction batteries to evolve beyond merely indicative academic studies into documentation based on more robust analysis. This study offers guidance as to where research and development (R&D) initiatives are likely to be rewarded with impact reductions.

A process-based attributional life cycle assessment (LCA) approach was used to report cradle-to-gate impact contributions in terms of the most relevant components. In order to avoid problem shifting, multiple impact categories were cov-

ered. In addition to the conventional LCA method, structural path analysis (SPA) was conducted to identify the most emission-intensive value chains (Peters and Hertwich 2006). The basic idea behind an SPA is the unraveling of the Leontief inverse by means of a series expansion, and this allows for impact investigation of different production chains (Wood and Lenzen 2009). This article is divided into five sections, including the “Introduction.” First, system definition, battery characteristics, and battery inventory are described. Thereafter, the main results of the cradle-to-gate analysis are presented. Subsequently, the findings are discussed and compared with preceding studies; in this section, some of the implications of the study are commented on. Finally, the main conclusions of the study are presented.

## Method

### System Definition


The study was a cradle-to-gate life cycle assessment of an NCM traction battery and the related background processes; other EV components were outside the system boundary. The functional unit was chosen as the production of one traction battery. Impacts were also reported for functional units based on mass measured in kilograms (kg) and in terms of nominal energy capacity measured in kilowatt-hours (kWh). A sensitivity analysis reporting battery production impacts per kilometer (km) driven was also included in order to investigate the influence of cycle life and powertrain efficiency on the environmental performance of the battery. A sensitivity analysis with respect to the source of the electricity was performed in order to assess how the electricity mix used in production influences the total impact.

### Battery Technology

Data in this section are provided by the battery producer (Miljøbil Grenland 2012). The battery is an NCM Li-ion battery for use in BEVs. Each battery cell is made with a cathode based on  $\text{Li}(\text{Ni}_x\text{Co}_y\text{Mn}_z)\text{O}_2$  and an anode based on graphite. One battery vehicle pack is made up of two battery subpacks connected in parallel. The weight of the battery is 253 kg, of which the battery cells makes up 60% of its total weight.<sup>1</sup> The battery's energy capacity is 26.6 kWh, and under normal use the battery efficiency is 95% to 96%.<sup>2</sup> The number of cycles the battery can perform before its nominal capacity falls below 80% of its initial rated capacity is often referred to as the battery's cycle life (Kalhammer et al. 2007). With 100% depth of discharge (DOD), the battery is expected to reach a nominal cycle life of 1,000 cycles, whereas 50% DOD extends the expected number to 5,000 cycles.

### Battery Manufacture

The battery components were grouped into four main components: battery cell; packaging; battery management system



**Figure 1** Simplified flow diagram of the battery system. BMS = battery management system; BMB = battery management board; IBIS = Integrated Battery Interface System.

(BMS); and cooling system. All of these components consisted of subcomponents (figure 1). The battery has 12 battery modules, each made up of 30 battery cells, for a total of 360 battery cells. Below, the inventory is described and comments are provided on the different components and subcomponents, beginning with the battery cells, then the packaging, the BMS, the cooling system, and finally the battery assembly process. The full inventory covering battery components can be found in the Supporting Information available on the Journal's Web site.

### Cell Manufacture

The battery cells consist of five subcomponents: anode; cathode; separator; electrolyte; and cell container. The bill of materials for the battery cell identified the material composition and weight of each of the battery cell subcomponents. The anode is composed of a copper current collector with a coat of negative electrode paste. The negative electrode paste consists mainly of synthetic graphite, but also contains small amounts of binders. The cathode is composed of an aluminum current collector with a coat of positive electrode paste. The positive electrode paste consists mainly of the positive active material,  $\text{Li}(\text{Ni}_x\text{Co}_y\text{Mn}_z)\text{O}_2$ , and small amounts of carbon black and a binder. In both the positive and negative electrode pastes, a solvent is applied to slurrify the mixtures; after the electrode mixtures have been applied to the current collectors the electrodes are baked and the solvent evaporates. To complete the production of the anode and cathode, the electrodes are fed

into slitting machines and cut to size. The electrolyte is based on the salt, lithium hexafluorophosphate ( $\text{LiPF}_6$ ), in a mixture of solvents. The separator is a porous polyolefin film. The cell container consists of a multilayer pouch and tabs. The pouch is placed around the cell components, with one end left open for electrolyte filling. After the electrolyte has been added and evenly distributed between the cathode, separator, and anode, the cell is sealed. For each cell, a copper tab is welded to the negative current collector and an aluminum tab welded to the positive current collector. The tabs pass through the walls of the sealed pouch and connect the cell to bar-shaped conductors, referred to as busbars.

The battery cell manufacturer provided information on their monthly electricity use for production over an 18-month period; the manufacturer's base cell is a 3.65 nominal voltage and 20-ampere-hour NCM type, which is the same as the studied battery, but the electricity use also includes other types of cells with various capacities. The energy requirements for battery cell manufacture include application of solvent to slurrify mixtures, coating of electrode pastes to metallic foils used as current collectors, baking of coated foils, slitting to size, welding of current collectors to tabs, filling of electrolyte, and initial charging of the finished cell, but according to the battery cell manufacturer, the predominant energy usage derives from operation of various dry rooms that are vital to the quality of the battery cells. There is significant variation in electricity use relative to production output over time, indicating that there is room for

improvement with respect to energy use. Three values for electricity use are presented in this work: the lower-bound value (LBV); the asymptotic value (ASV); and the average value (AVV). The LBV is the value for the most energy-efficient month at 586 megajoules (MJ) per kWh (MJ/kWh) battery cell capacity produced,<sup>3</sup> the ASV represents the asymptotic value for the data set at 960 MJ/kWh battery cell<sup>-1</sup>, and the AVV is the average value for the data set at 2,318 MJ/kWh battery cell<sup>-1</sup>.

### Packaging

Packaging is divided into three subcomponents: module packaging; battery retention; and battery tray. The module packaging consists of inner and outer frames, the aforementioned busbars, module fasteners, and a module lid. The inner and outer frames form nylon cassettes that are placed around the battery cell container to provide protection and structural support. Additionally, each frame includes an aluminum heat transfer plate to ensure optimal thermal conduction. Thirty cassettes stacked after one another form a battery module. At the top of the cassettes, the tabs are welded to the busbars. For the total of 60 tabs per module, there are 30 busbars. There are three types of busbars: copper end busbars; aluminum end busbars; and bimetallic busbars. Bimetallic busbars have a copper side and an aluminum side. At the negative terminal of the battery, an end-busbar holder with a copper busbar is followed by seven double busbar holders, each with two bimetallic busbars, adding up to a total of 15 busbars. Similarly, on the positive terminal, an end-busbar holder with one aluminum busbar is followed by seven double busbar holders, each with two bimetallic busbars, also adding up to 15 busbars. The module fasteners include steel screws, caps, nuts, and retention rods, as well as nylon washers. Together with the module lid, the fasteners are used for assembly of the individual battery modules. There are 12 battery modules in one battery, and the battery retention system keeps the battery modules in place within the battery tray, using straps, restraints, and foams. In addition, eight heat transfer plates made of steel are considered a part of the battery retention system. All battery components are placed inside a steel battery tray, which is closed with a sealed lid.

### Battery Management System

The BMS includes battery module boards (BMBs), the Integrated Battery Interface System (IBIS), fasteners, a high-voltage (HV) system, and a low-voltage system. In each battery, there are 12 BMBs, one for each module. BMBs are placed under module lids, situated between the two rows of busbars. The BMBs monitor the battery cells for voltage and temperature limits, whereas the IBIS acts as a master controller for the BMBs, as well as overseeing the battery charge and discharge strategies. Additionally, the IBIS provides vehicle-level HV precharge, contactor control, system isolation monitoring, and charge/discharge current measurements. Attached with steel screws, the IBIS box is an integrated part of the HV system, which also contains cables, nylon clips, intermodule fuse, neoprene gaskets, both plastic and aluminum connectors, and an

aluminum lid. The low-voltage system consists of nylon clips and harnesses.

### Cooling System

For thermal management, the battery is equipped with a cooling system. An aluminum radiator is the main component of the cooling system. For the convective heat medium, the cooling system includes a glycol coolant, which is contained within aluminum manifolds. Clamps and fasteners made of steel as well as pipe fittings of plastic and rubber are used for sealing. Thermal conductivity is further ensured with the use of a thermal gap pad made of fiberglass-reinforced filler and polymer.

### Battery Assembly

Battery assembly is performed at Miljøbil Grenland's facility. The assembly process itself requires little energy because the assembly of battery components to make one battery pack is mainly performed using manual labor. The only direct energy requirement is for a welding process, which only amounts to 0.014 MJ/kWh of battery capacity.

### Inventory

An overview of the inventoried battery components are listed in table 1. The inventory list indicates the extent of original data collected for this study and which data are gathered from the literature. Forty-two elements are original data, whereas five are taken from Majeau-Bettez and colleagues (2011) and two from Notter and colleagues (2010)/Ecoinvent 2.2. The subinventory for the positive active material was based on Majeau-Bettez and colleagues (2011), but the ratio of nickel, cobalt, and manganese has been modified from  $\text{Li}(\text{Ni}_{0.4}\text{Co}_{0.2}\text{Mn}_{0.4})\text{O}_2$  to  $\text{Li}(\text{Ni}_{1/3}\text{Co}_{1/3}\text{Mn}_{1/3})\text{O}_2$  (c.f., Ngala et al. 2004; Huang et al. 2011; Väyrynen and Salminen 2012; Wang and Chen 2012; Huang and Hitt 2013). Otherwise, no modifications have been made to the original subinventories.

Copper products, in our study, were modeled as 85% of primary and 15% secondary copper, a division based on the average copper consumption mix (International Institute for Sustainable Development 2010). Aluminum products were modeled as a production mix consisting of 68% primary aluminum, 10% secondary aluminum from old scrap, and 22% secondary aluminum from new scrap (Ecoinvent Centre 2010). Steel products were modeled as low-alloyed steel, where 49% is made from recycled material (Ecoinvent Centre 2010). For the manufacture of battery cells, we established a medium voltage electricity mix, based on the following sources: 46% coal; 33% nuclear; 15% gas; 4.4% oil; 1.4% hydro; 0.15% wind; 0.12% solar photovoltaic; and 0.044% waste incineration. The assembly of the battery is performed in Norway, and thus the Norwegian electricity mix, at medium voltage, was used for the welding process. Transport was modeled as receiver input and was mainly based on standard transport distances of materials (Ecoinvent Centre 2010). The transportation of battery cells and module packaging from the cell manufacturer in East Asia to Miljøbil Grenland in Norway included road transport and ocean freight. Choice of infrastructure required for production of the battery,

**Table 1** List of inventories and subinventories

	<i>Inventory list</i>
1	One battery pack
2	Battery packaging
3	BMS
4	Cooling system
5	Battery cell
6	Battery tray
7	Battery retention
8	Tray with fasteners
9	Tray lid
10	Tray seal
11	Strap retention
12	Lower retention
13	Propagation plate
14	Low voltage system
15	High voltage system
16	Fasteners
17	Integrated Battery Interface System (IBIS)
18	Radiator
19	Manifolds
20	Clamps
21	Pipe fitting
22	Thermal pad
23	Module packaging
24	Module fasteners
25	Outer frame
26	Inner frame
27	Bimetallic busbars, Al and Cu
28	Busbars, Al
29	Busbars, Cu
30	Module lid
31	Electrolyte
32	Cathode
33	Anode
34	Cell container
35	Separator
36	Positive current collector, Al
37	Positive electrode paste
38	Negative current collector, Cu
39	Negative electrode paste
40	Tab, Al
41	Tab, Cu
42	Aluminum pouch
43	Positive active material <sup>a</sup>
44	Nickel cobalt manganese hydroxide <sup>a</sup>
45	Nickel sulfate <sup>a</sup>
46	Cobalt sulfate <sup>a</sup>
47	Manganese sulfate <sup>a</sup>
48	Lithium hexafluorophosphate <sup>b</sup>
49	Synthetic graphite <sup>b</sup>

<sup>a</sup>Majeau-Bettez and colleagues (2011).

<sup>b</sup>Notter and colleagues (2010).

BMS = battery management system; Al = aluminum; Cu = copper.

battery components, and subcomponents was estimated based on the recommendations published in the *Ecoinvent* reports (Ecoinvent Centre 2010).

Our inventory was linked to *Ecoinvent 2.2* as a background system (Ecoinvent Centre 2010) and included materials from resource extraction. Using process-based attributional LCA, the cradle-to-gate impacts of the battery were calculated from the compiled inventory. The battery was not attributed any benefits from second-life or end-of-life treatment. Characterization of environmental releases and resource use was performed using the ReCiPe characterization method (version 1.08) for mid-point indicators from the hierarchical perspective (Goedkoop et al. 2009). SPA was performed to identify the value chain of the most emission-intensive processes and components.

## Results and Analysis

In this section, the environmental impacts associated with the production of the battery are presented. The total impact of the battery for 13 impact categories with additional results for two alternative functional units is reported on (table 2), and the cradle-to-gate impact contributions are broken down in terms of key components (figure 2). The results of a sensitivity analysis shows how different parameters influence the manner in which production impacts are spread out over the use phase (figure 3). Another sensitivity analysis shows the impact of different electricity sources used for the manufacture of battery cells (figure 4).

### Total Impacts and Contribution Analysis

The cradle-to-gate impact of our battery is highly dependent upon the energy requirements of battery cell manufacture. Therefore, impact at the LBV, ASV, and AVV of the battery are all reported on (table 2). At the LBV, the cradle-to-gate global warming potential (GWP) of the battery is 4.6 tonnes carbon dioxide equivalents (CO<sub>2</sub>-eq.), whereas at the ASV it is 6.4 tonnes CO<sub>2</sub>-eq, and at the AVV it is 13.0 tonnes CO<sub>2</sub>-eq.<sup>4</sup>


The results will hereafter be discussed in terms of the LBV, because this is likely to better reflect large-scale production volumes. The cradle-to-gate production impacts of the battery are mainly caused by the production chains of three key requirements: the manufacture of battery cells; the positive electrode paste; and the negative current collector (figure 2). For the various impact categories, these three production chains combined comprise 56% to 87% of the battery's total impact. With the use of SPA, the value chains are tracked to find the different sources of impacts. Combustion of hard coal and natural gas in power plants to meet the energy requirements for the manufacture of battery cells make up 51% of the battery's total GWP impact. Extraction of hard coal and natural gas for the same purpose make up 32% of the battery's total fossil depletion potential (FDP). Natural gas, uranium, and crude oil, which are also used to meet the energy requirements for battery cell production, contribute to 31% of the battery's total ozone

**Table 2** Total impact of production


Impact	Units	Functional unit One battery pack			Alternative functional units					
		LBV	ASV	AVV	Mass [kg <sup>-1</sup> ]			Cycle capacity [kWh <sup>-1</sup> ]		
					LBV	ASV	AVV	LBV	ASV	AVV
GWP <sub>100</sub>	kg CO <sub>2</sub> -eq	4,580	6,390	12,960	18	25	51	172	240	487
FDP	kg oil-eq	1,320	1,820	3,630	5.2	7.2	14	49.5	68.3	136.6
ODP <sub>inf</sub>	kg CFC-11-eq	2.8E-04	3.6E-04	6.5E-04	1.1E-06	1.4E-06	2.6E-06	1.1E-05	1.4E-05	2.4E-05
POFP	kg NMVOC	18	22	38	7.2E-02	8.9E-02	1.5E-01	6.8E-01	8.4E-01	1.4E+00
PMFP	kg PM10-eq	16	18	26	6.1E-02	7.0E-02	1.0E-01	5.8E-01	6.7E-01	9.7E-01
TAP <sub>100</sub>	kg SO <sub>2</sub> -eq	51	59	85	2.0E-01	2.3E-01	3.4E-01	1.9	2.2	3.2
FEP	kg P-eq	8.0	8.7	11.0	3.2E-02	3.4E-02	4.4E-02	3.0E-01	3.3E-01	4.2E-01
MEP	kg N-eq	6.4	6.7	7.8	2.5E-02	2.6E-02	3.1E-02	2.4E-01	2.5E-01	2.9E-01
FETP <sub>inf</sub>	kg 1,4-DCB-eq	256	267	308	1.0	1.1	1.2	9.6	10.0	11.6
METP <sub>inf</sub>	kg 1,4-DCB-eq	276	287	329	1.1	1.1	1.3	10.4	10.8	12.4
TETP <sub>inf</sub>	kg 1,4 DCB-eq	1.3	1.4	1.6	5.2E-03	5.4E-03	6.2E-03	5.0E-02	5.2E-02	5.9E-02
HTP <sub>inf</sub>	kg 1,4-DCB-eq	15,900	16,340	18,110	63	64	71	596	614	681
MDP	kg Fe-eq	4,100	4,120	4,180	16	16	17	154	155	157

Note: Impact categories: global warming potential (GWP), fossil depletion potential (FDP), ozone depletion potential (ODP), photo oxidation formation potential (POFP), particulate matter formation potential (PMFP), terrestrial acidification potential (TAP), freshwater eutrophication potential (FEP), marine eutrophication potential (MEP), freshwater toxicity potential (FETP), marine toxicity potential (METP), terrestrial eutrophication potential (TETP), human toxicity potential (HTP), and metal depletion potential (MDP). Suffixes “eq,” “100,” and “inf” refer to equivalents, 100 years, and infinity, respectively.


kg eq = kilograms equivalents; LBV = lower-bound value; ASV = asymptotic value; AVV = average value; kWh = kilowatt-hour; CO<sub>2</sub> = carbon dioxide; CFC-11 = trichlorofluoromethane; NMVOC = nonmethane volatile organic carbon; PM10 = particulate matter less than 10 μm in diameter; SO<sub>2</sub> = sulfur dioxide; P = phosphor; N = nitrogen; 1,4-DCB = 1,4-dichlorobenzene; Fe = iron.



**Figure 2** Contribution of cradle-to-gate impacts of the battery. Impact categories: global warming potential (GWP), fossil depletion potential (FDP), ozone depletion potential (ODP), photo oxidation formation potential (POFP), particulate matter formation potential (PMFP), terrestrial acidification potential (TAP), freshwater eutrophication potential (FEP), marine eutrophication potential (MEP), freshwater toxicity potential (FETP), marine toxicity potential (METP), terrestrial eutrophication potential (TETP), human toxicity potential (HTP), and metal depletion potential (MDP). Suffixes “eq,” “100,” and “inf” refer to equivalents, 100 years, and infinity, respectively. CO<sub>2</sub> = carbon dioxide; CFC-11 = trichlorofluoromethane; NMVOC = nonmethane volatile organic carbon; PM10 = particulate matter less than 10 μm in diameter; SO<sub>2</sub> = sulfur dioxide; P = phosphor; N = nitrogen; 1,4-DCB = 1,4-dichlorobenzene; Fe = iron.



**Figure 3** Sensitivity analysis on production impacts spread out over the use phase. Impact category: global warming potential (GWP). Suffixes “eq” and “100” refer to equivalents and 100 years, respectively. Abbreviations: g = gram; CO<sub>2</sub> = carbon dioxide; MJ = megajoule; km = kilometer.



**Figure 4** Sensitivity analysis with respect to source of electricity for battery cell manufacture. Impact category: global warming potential (GWP). Suffixes “eq” and “100” refer to equivalents and 100 years, respectively. Abbreviations: kg = kilogram; CO<sub>2</sub> = carbon dioxide; NG = natural gas; Current el. mix = Current electricity mix.

depletion potential (ODP). Most impacts from the positive electrode paste are predominantly the result of the use of nickel sulfate, but manganese causes 86% of the paste’s metal depletion potential (MDP). It should be noted that the ReCiPe method does not include a depletion characterization factor for lithium, and therefore the use of lithium has no MDP impact, which, in turn, results in an underestimated absolute MDP value in

this study (see “*Insights and implications*” below). Primary copper used in the negative current collector adds a large share of the battery’s total impact for many midpoint categories; it indirectly causes the disposal of sulfidic tailings that are to blame for 62% of freshwater eutrophication potential (FEP), 65% of freshwater ecotoxicity potential (FETP), 54% of marine ecotoxicity potential (METP), and 53% of human toxicity

potential (HTP). The solvent, *N*-methyl-2-pyrrolidone (NMP), used in both the positive and negative electrode paste, causes the only significant contribution of the negative paste; production of dimethylamine used in the solvent contributes to 75% of the battery's total marine eutrophication potential (MEP).

### Sensitivity Analyses

To establish the GWP impact for a given distance driven, the total production impact of the battery is divided by the total distance the battery covers during its operating life in the vehicle. For a given initial nominal energy capacity, the distance is dependent upon the battery's cycle life and the powertrain efficiency of the EV. For figure 3, an 80% DOD and a capacity loss of 0.008% per cycle from its initial capacity (see the Supporting Information on the Web) were assumed.

The impact of production measured in grams (g) per km (g/km) is a decaying function of cycle number; because the battery deteriorates slowly, doubling the number of charge-discharge cycles in the battery's use phase almost doubles the driving distance for the same initial impact (figure 3). Lower cycle numbers can be crucial for whether a BEV is environmentally preferable to an ICEV or not. Studies assessing the environmental performance of batteries can reach different conclusions, all depending on the assumptions regarding battery cycle numbers or range; for our battery, a battery lifetime of 3,000 cycles (Majeau-Bettez et al. 2011) with a powertrain efficiency of 0.50 MJ/km results in 11 g CO<sub>2</sub>-eq/km<sup>-1</sup>, whereas a lifetime of 150,000 km (Notter et al. 2010), results in 31 g CO<sub>2</sub>-eq/km<sup>-1</sup>.<sup>5</sup>

Figure 3 also shows how, for a given number of charge-discharge cycles, different powertrain efficiencies allow for different driving distances with the same initial battery production impact. For example, relative to a powertrain efficiency of 0.5 MJ/km<sup>-1</sup> as a starting point, every 0.1 MJ/km<sup>-1</sup> change in powertrain efficiency yields a 20% change in attributed production impact per km for any given cycle number.

Energy requirements met with a highly carbon-intensive electricity mix result in large GWP impacts (figure 4). The largest energy requirements in the production of the battery are found in the manufacture of battery cells, and thus a sensitivity analysis with respect to the electricity used in the production of the cells is performed. In the first scenario, the battery cells are produced with electricity based on coal, which results in an increase of the battery's GWP by more than 40%. In the second scenario, the electricity is based on natural gas, which has similar carbon intensity as the current electricity mix and thus results in insignificant change in GWP. In the last scenario, the battery cells are produced using electricity based on hydroelectric power, which leads to a more than 60% decrease, compared to the battery's current GWP.

## Discussion

### Result Analysis and Comparison with Preceding Studies

The aim of the study is to provide a detailed LCI of an NCM traction battery and report direct and indirect impacts of

production for this battery. Battery capacity measured in kWh is used as a representative functional unit for batteries, which allows a consistent comparison of the studies. Data from preceding Li-ion traction battery studies have been compiled and include energy density of cell, direct energy requirements for cell manufacture in terms of MJ/kWh, GWP resulting from direct energy use in cell manufacture, and GWP of the entire battery (table 3). Note that the focus is on the cell (not the battery), because energy requirements are significantly higher in cell production than in battery assembly.

The reported energy required for manufacture of battery cells from preceding studies varies greatly, from 3.1 to 1,060 MJ/kWh<sup>-1</sup> (table 3). At the LBV, the present study reports the corresponding energy requirements to be 586 MJ/kWh<sup>-1</sup>. Notter and colleagues (2010) made their own process-based energy estimations. Bauer (2010), Zackrisson and colleagues (2010), and Majeau-Bettez and colleagues (2011) based their energy data on industry reports from Hitachi Maxell (2003, 2005), Saft (2008), and Rydh and Sandén (2005), respectively. Note that energy data reported in Zackrisson and colleagues (2010) and Majeau-Bettez and colleagues (2011) include battery assembly as well as cell manufacture. Dunn and colleagues (2012b) based their energy data on a quote for a dry room (provided by dry room manufacturer SCS Systems) and calculated energy required for formation cycling (Dunn et al. 2012a). The USEPA (2013) based their energy data partly on proprietary industry sources and partly on Majeau-Bettez and colleagues (2011). The process-level approach, used by Dunn and colleagues (2012b) and Notter and colleagues (2010), has the advantage of being process specific and yields detailed results, but runs the risk of leaving out processes, and the lack of access to primary data may lead to uncertain estimates. The top-down approach, used by Bauer (2010), Zackrisson and colleagues (2010), and Majeau-Bettez and colleagues (2011) has the advantage of being complete with respect to inclusion of all relevant activities related to the producing industry, but data are often aggregated, which results in a lack of detail, and may include inhomogeneous products. In our study, the system boundaries for the battery cell manufacture are well defined and products are homogenous (produces only Li-ion battery cells), and thus we used a top-down approach to establish energy usage. The different approaches have resulted in two opposing understandings; we align with Bauer (2010), Zackrisson and colleagues (2010), and Majeau-Bettez and colleagues (2011) and find significantly higher energy requirements than Dunn and colleagues (2012b), Notter and colleagues (2010), and the USEPA (2013).

The environmental impacts of the cradle-to-gate analysis for the LBV are compared with results reported in preceding studies, but only limited comparison can be made with Bauer (2010) and Dunn and colleagues (2012b) because they report results for materials rather than components. There will be a stronger emphasis on GWP than other impact categories, owing both to GWP being the only common impact category in the reviewed literature, and the fact that EVs, to a large extent, are being promoted precisely as an alternative to ICEVs in order to reduce GWP. The preceding studies report a wide range of

**Table 3** Cell data

Study	Cell energy density (kWh/kg)	Direct use in cell manufacture (MJ/kWh)	GWP resulting from direct energy use in cell manufacture (kg CO <sub>2</sub> -eq/kWh)	GWP of battery (kg CO <sub>2</sub> -eq/kWh)	Energy reference
Notter et al. (2010)	0.143	3.1	0.90	53	Authors' own estimates
Bauer (2010)	0.069–0.176	326–1,062	50–152	133–338	Hitachi Maxell (2003, 2005)
Zackrisson et al. (2010) <sup>a</sup>	0.103–0.104	790–791	55–141	166–266	Saft (2008)
Majeau-Bettez et al. (2011) <sup>a</sup>	0.110–0.140	371–473	56–70	200–250	Rydh and Sandén (2005)
Dunn et al. (2012b) <sup>b</sup>	0.148	10.7	2.3	38	Dunn and colleagues (2012a); Tagawa and Brodd (2009)
USEPA (2013) <sup>c</sup>	0.139–0.167	0–28.3	0–1.8	63–151	Proprietary; Majeau-Bettez and colleagues (2011)
This article LBV	0.174	586	107	172	Primary
This article ASV	0.174	960	175	240	Primary
This article AVV	0.174	2,318	424	487	Primary

<sup>a</sup>The studies have a combined cell and battery manufacturing process, and thus energy inputs and GWP shares include both.

<sup>b</sup>Total weight of cells is assumed to be 90% of total battery weight.

<sup>c</sup>Total weight of cell is assumed to be 60% of total battery weight

kWh = kilowatt-hour; kg = kilogram; MJ = megajoule; CO<sub>2</sub>-eq = carbon dioxide equivalents; LBV = lower bound value; ASV = asymptotic value; AVV = average value.

impacts: 53 to 338 kg CO<sub>2</sub>-eq/kWh<sup>-1</sup> of nominal capacity. In comparison, our production impact is found to be 172 kg CO<sub>2</sub>-eq/kWh<sup>-1</sup>.

We use the same inventory, with only a small alteration, for the positive active material as Majeau-Bettez and colleagues (2011) did for their NCM battery. Despite the common data, the GWP impact of the positive electrode paste reported in our study is nearly one fifth of what Majeau-Bettez and colleagues (2011) found; their high impact is the result of the binder used in their study. The total ODP obtained in their study is more than two orders of magnitude higher than ours and nearly all of their ODP impact is attributed to the binder material. Majeau-Bettez and colleagues (2011) assumed polytetrafluoroethylene (PTFE) as binder and used tetrafluoroethylene (TFE) as a proxy, which the researchers mentioned as having a high GWP, and particularly high ODP impact. In contrast, we use polyvinyl fluoride as a proxy for polyvinylidene fluoride. Our study reports similar overall impact of the positive current collector as Majeau-Bettez and colleagues (2011). We obtain twice as high GWP impact for the positive electrode paste, compared to Notter and colleagues (2010), and this is likely the result of differences in the active materials. Notter and colleagues (2010) estimated the weight of the positive current collector to be more than four times heavier than those in our battery and consequently report GWP more than four times larger than our study. Zackrisson and colleagues (2010) report the GWP impact of the cathode, made with water rather than NMP, to be similar to ours. Compared to our cathode, the USEPA (2013) reports impacts twice

as high for their NCM cathode, likely explained by the higher share of cathode materials in their battery.

Majeau-Bettez and colleagues (2011) report GWP impacts of the negative electrode paste around four times larger than the paste in our battery, which is also likely to be the result of the use of PTFE as a binder. For our battery, MEP resulting from the negative electrode paste is caused by production of dimethylamine used in NMP. The amount of NMP in our battery is larger than what Majeau-Bettez and colleagues (2011) estimated in their study, and this explains their lower MEP impact. Because our negative current collectors are heavier than those in Majeau-Bettez and colleagues (2011), there is higher overall impact. For the anode, with water as solvent, Zackrisson and colleagues (2010) find the GWP to be nearly seven times smaller than the anode in our battery. A possible explanation is that only 4.8% of the battery cell's weight is from the negative current collectors in the Zackrisson and colleagues (2010) study, compared to 22% in our battery. Both Notter and colleagues (2010) and the USEPA (2013) obtain similar GWP for the anode as we do.

The lack of access to industry data in the preceding studies is perhaps more evident for the packaging and the BMS components than the other battery components. The reported GWP resulting from packaging is three to nine times higher for our battery than the preceding studies. For the BMS inventory, there is great variability in the literature. Compared to our BMS, Majeau-Bettez and colleagues (2011) and Zackrisson and colleagues (2010) report three to four times larger GWP, whereas

the USEPA (2013) and Dunn and colleagues (2012b) estimate half the impact of ours. The BMS impact reported by Notter and colleagues (2010) is similar to the impact of our BMS.

The USEPA (2013) reported the impact of a cooling system aggregated with the BMS impact. Dunn and colleagues (2012b) included glycol as a coolant fluid, but beyond this did not make an inventory for a cooling system. Because the cooling system is a rather uncomplicated component material-wise and the inventory is based on primary industry data, we are confident in the relatively low (5% of total GWP) impact generated by the cooling system.

### Insights and Implications

The production of the battery requires five kg of lithium.

It is deemed unlikely that lithium in the battery will be recycled, because only selected materials, such as nickel and cobalt, are being recycled from Li-ion batteries (Dewulf et al. 2010). At present, the recovery of lithium is not efficient because of the low lithium content in batteries and the present low prices for lithium ore (Ziemann et al. 2012). Grosjean and colleagues (2012) and Mohr and colleagues (2012) assessed the world lithium resources and concluded that despite the technological breakthrough of EVs, the planet is in no danger of running out of lithium. In the study by Notter and colleagues (2010), it was concluded that although lithium can be considered to be a geochemically scarce metal, assessment with abiotic depletion potential does not result in a high impact for the lithium components of their battery.

By using our findings as a guide, the battery industry can reduce the environmental footprint of traction batteries. GWP of the battery will be reduced if the energy requirements are decreased or met with less carbon-intensive electricity. The sensitivity analysis showed that it was possible to reduce the impact of production by more than 60% if the electricity used in cell manufacture was based on hydroelectric power, rather than the current electricity mix. For the studied NCM battery, the positive electrode paste and the negative current collector made of copper have particularly high environmental impacts and reuse of these components is desirable because adverse environmental effects can thereby be avoided. The current battery technology has a limited functional lifetime; ideally, the batteries should last at least as long as the vehicles they drive. Extending the battery life may eliminate the necessity of replacement in the vehicle lifetime, making the achievable cycle number of the battery a crucial parameter. The sensitivity analysis performed on cycle number and impact per km driven (figure 3) shows that not only total number of cycles delivered by the battery is important, but that powertrain efficiency is also a crucial parameter. To drive a distance of 160,000 km (total driving distance given for the Mercedes-Benz A 180), 1,100 cycles will be demanded of the battery by a vehicle with powertrain efficiency of 0.50 MJ/km, whereas 1,800 cycles will be demanded by a vehicle with powertrain efficiency of 0.80 MJ/km. This demonstrates that the number of cycles required from the battery by the vehicle is dependent on the powertrain efficiency of the ve-

hicle. In this way, the powertrain efficiency directly influences the usable lifetime of the battery in the vehicle (figure 3).

The production of the battery causes 4.6 tonnes CO<sub>2</sub>-eq at LBV (table 2). This is close to the cradle-to-gate impact of a small personal vehicle, such as the A 180, which emits 6.1 tonnes CO<sub>2</sub>-eq (Daimler AG 2012). In fact, production of EVs have been found to have almost twice as large a GWP as ICEVs (Hawkins et al. 2013; Volkswagen AG 2013). In order for EVs to be a viable alternative from a GWP perspective, EVs have to make up for the large production phase impacts by emitting less than ICEVs in the use phase.

### Conclusion

A high-resolution inventory for an NCM traction battery has been compiled. In addition, the environmental impacts associated with the production of the studied battery are assessed and analyzed (table 2). The most impact-intensive production chains were the manufacture of the battery cells, the positive electrode paste, and the negative current collector (figure 2). Our main findings were comparable with those in preceding studies; the observed discrepancies between our study and the preceding studies can, to a large extent, be explained by the differences in battery design or the preceding studies' lack of access to primary data. Sensitivity analysis showed that powertrain efficiency and cycle numbers are crucial when assessing the environmental impact of traction batteries (figure 3). The sensitivity analysis of electricity used for manufacture of battery cells showed that the most effective approach to reduce GWP is to focus on reducing the energy demand in cell manufacture and the carbon intensity of the electricity used in production (figure 4).

If the battery industry and policy makers use our results to prioritize R&D resources—decreasing the manufacturing energy requirements or using cleaner electricity sources, closing the material loop by recycling, and increasing the battery lifetime—impacts may be reduced to the point where EVs offer very clear advantages relative to ICEVs. EV producers, in turn, may improve the battery lifetime by improving powertrain efficiency.

With this work, original primary data are provided, and by doing so, some of the key gaps in the existing literature on EVs, and particularly on traction batteries, are filled. Consequently, the study allows for a better understanding of the environmental impacts pertaining to traction batteries and, ultimately, EVs and permits the discussion of traction batteries to move forward with a greater empirical foundation.

### Acknowledgments

This research was made possible, in part, by the Norwegian Research Council under the E-Car project and CenSES.

### Notes

1. One kilogram (kg, SI)  $\approx$  2.204 pounds (lb).

2. One kilowatt-hour (kWh)  $\approx 3.6 \times 10^6$  joules (J, SI)  $\approx 3.412 \times 10^3$  British Thermal Units (BTU).
3. One megajoule (MJ) =  $10^6$  joules (J, SI)  $\approx 239$  kilocalories (kcal)  $\approx 948$  British Thermal Units (BTU).
4. One tonne (t) =  $10^3$  kilograms (kg, SI)  $\approx 1.102$  short tons. Carbon dioxide equivalent (CO<sub>2</sub>-eq) is a measure for describing the climate-forcing strength of a quantity of greenhouse gases using the functionally equivalent amount of carbon dioxide as the reference.
5. One gram (g) =  $10^{-3}$  kilograms (kg, SI)  $\approx 0.035$  ounces (oz). One kilometer (km, SI)  $\approx 0.621$  miles (mi).

## References

- Bauer, C. 2010. *Ökobilanz von Lithium-Ionen Batterien. [Life cycle assessment of lithium-ion batteries.] Assessment*. Paul Scherrer Institut, Labor für Energiesystem-Analysen. [http://gabe.web.psi.ch/pdfs/PSI\\_Report/OekobilanzLiIonBatterien\\_PSI\\_Schlussbericht\\_2010.pdf](http://gabe.web.psi.ch/pdfs/PSI_Report/OekobilanzLiIonBatterien_PSI_Schlussbericht_2010.pdf). Accessed 13 November 2012.
- Cameán, I., P. Lavela, J. L. Tirado, and A. B. García. 2010. On the electrochemical performance of anthracite-based graphite materials as anodes in lithium-ion batteries. *Fuel* 89(5): 986–991.
- Daimler AG. 2012. *Environmental certificate Mercedes-Benz A-class*. Stuttgart, Germany: Global Communications Mercedes-Benz Cars. [www.daimler.com/Projects/c2c/channel/documents/2240746\\_Environmental\\_Certificate\\_Mercedes-Benz\\_A\\_Class.pdf](http://www.daimler.com/Projects/c2c/channel/documents/2240746_Environmental_Certificate_Mercedes-Benz_A_Class.pdf). Accessed 16 June 2012.
- Dewulf, J., G. van der Vorst, K. Denturck, H. van Langenhove, W. Ghyoot, J. Tytgat, and K. Vandeputte. 2010. Recycling rechargeable lithium ion batteries: Critical analysis of natural resource savings. *Resources, Conservation and Recycling* 54(4): 229–234.
- Dunn, J. B., M. Barnes, L. Gaines, J. Sullivan, and M. Q. Wang. 2012a. *Material and energy flows in the materials production, assembly, and end-of-life stages of the automotive lithium-ion battery life cycle*. <http://greet.es.anl.gov/publication-lib-lca>. Accessed 30 April 2013.
- Dunn, J. B., L. Gaines, J. Sullivan, and M. Q. Wang. 2012b. Impact of recycling on cradle-to-gate energy consumption and greenhouse gas emissions of automotive lithium-ion batteries. *Environmental Science & Technology* 46(22): 12704–12710.
- Ecoinvent Center. 2010. *Ecoinvent data and reports v.2.2*. Dübendorf, Switzerland: Swiss Center for Life Cycle Inventories.
- Goedkoop, M., R. Heijungs, M. Huijbregts, A. De Schryver, J. Struijs, and R. van Zelm. 2009. *ReCiPe 2008. A life cycle impact assessment method which comprises harmonised category indicators at the midpoint and the endpoint level*. First edition report I: Characterisation. The Netherlands: Ministerie van VROM. <http://www.lcia-recipe.net/>. Accessed 4 June 2013.
- Grosjean, C., P. H. Miranda, M. Perrin, and P. Poggi. 2012. Assessment of world lithium resources and consequences of their geographic distribution on the expected development of the electric vehicle industry. *Renewable and Sustainable Energy Reviews* 16(3): 1735–1744.
- Hawkins, T. R., B. Singh, G. Majeau-Bettez, and A. H. Strømman. 2013. Comparative environmental life cycle assessment of conventional and electric vehicles. *Journal of Industrial Ecology* 17(1): 53–64.
- Hitachi Maxell Ltd. 2003. *Annual report*. Tokyo, Japan: Hitachi Group.
- Hitachi Maxell Ltd. 2005. *Environmental report*. Tokyo, Japan: Hitachi Group.
- Huang, X. and J. Hitt. 2013. Lithium ion battery separators: Development and performance characterization of a composite membrane. *Journal of Membrane Science* 425–426: 163–168.
- Huang, Z.-D., X.-M. Liu, B. Zhang, S.-W. Oh, P.-C. Ma, and J.-K. Kim. 2011. LiNi<sub>1/3</sub>Co<sub>1/3</sub>Mn<sub>1/3</sub>O<sub>2</sub> with a novel one-dimensional porous structure: A high-power cathode material for rechargeable Li-ion batteries. *Scripta Materialia* 64(2): 122–125.
- IISD (International Institute for Sustainable Development). 2010. *Sustainable development and the global copper supply chain: International research team report*. Toronto, Canada: Five Winds International.
- Kalhammer, F. R., B. M. Kopf, D. H. Swan, V. P. Roan, and M. P. Walsh. 2007. *Status and prospects for zero emissions vehicle technology*. Sacramento, CA, USA: State of California Air Resources Board.
- Majeau-Bettez, G., T. R. Hawkins, and A. H. Strømman. 2011. Life cycle environmental assessment of lithium-ion and nickel metal hydride batteries for plug-in hybrid and battery electric vehicles. *Environmental Science & Technology* 45(10): 4548–4554.
- Miljøbil Grenland. 2012. *Bill of materials*. Porsgrunn, Norway.
- Mohr, S. H., G. Mudd, and D. Giurco. 2012. Lithium resources and production: Critical assessment and global projections. *Minerals* 2(1): 65–84.
- Ngala, J. K., N. A. Chernova, M. Ma, M. Mamak, P. Y. Zavalij, and M. S. Whittingham. 2004. The synthesis, characterization and electrochemical behavior of the layered LiNi<sub>0.4</sub>Mn<sub>0.4</sub>Co<sub>0.2</sub>O<sub>2</sub> compound. *Journal of Materials Chemistry* 14(2): 214–220. <http://xlink.rsc.org/?DOI=b309834f>. Accessed 13 September 2010.
- Notter, D. A., M. Gauch, R. Widmer, P. Wäger, A. Stamp, R. Zah, and H.-J. Althaus. 2010. Contribution of Li-ion batteries to the environmental impact of electric vehicles. *Environmental Science & Technology* 44(17): 6550–6556.
- Park, T.-H., J.-S. Yeo, M.-H. Seo, J. Miyawaki, I. Mochida, and S.-H. Yoon. 2013. Enhancing the rate performance of graphite anodes through addition of natural graphite/carbon nanofibers in lithium-ion batteries. *Electrochimica Acta* 93: 236–240.
- Peters, G. P. and E. G. Hertwich. 2006. Structural analysis of international trade: Environmental impacts of Norway. *Economic Systems Research* 18(2): 155–181.
- Rydh, C. J. and B. A. Sandén. 2005. Energy analysis of batteries in photovoltaic systems. Part I: Performance and energy requirements. *Energy Conversion and Management* 46(11–12): 1957–1979.
- Saft. 2008. *Annual report 2008. Management*. Bagnolet, France: Saft Group SA.
- Samaras, C. and K. Meisterling. 2008. Life cycle assessment of greenhouse gas emissions from plug-in hybrid vehicles: Implications for policy. *Environmental Science & Technology* 42(9): 3170–3176.
- Solomon, S., D. Qin, M. Manning, Z. Chen, M. Marquis, K. B. Averyt, M. Tignor, and H. L. Miller. 2007. *Contribution of Working Group I to the Fourth Assessment Report of the Intergovernmental Panel on Climate Change*. Cambridge, UK: Cambridge University Press.
- USEPA (United States Environmental Protection Agency). 2013. *Application of life-cycle assessment to nanoscale technology: Lithium-ion batteries for electric vehicles*. EPA 744-R-12-001. Washington, DC: National Service Center for Environmental Publications. [www.epa.gov/dfe/pubs/projects/lbnp/final-li-ion-battery-lca-report.pdf](http://www.epa.gov/dfe/pubs/projects/lbnp/final-li-ion-battery-lca-report.pdf). Accessed 20 May 2013.
- Volkswagen AG. 2013. *The e-mission. Electric mobility and the environment. Production*. [www.volkswagenag.com/content/vwcorp/info\\_center/en/publications/2013/01/The\\_e-Mission\\_Electric\\_Mobility\\_and\\_the\\_Environment.bin.html/binarystorageitem/file/the\\_e-mission.pdf](http://www.volkswagenag.com/content/vwcorp/info_center/en/publications/2013/01/The_e-Mission_Electric_Mobility_and_the_Environment.bin.html/binarystorageitem/file/the_e-mission.pdf). Accessed 12 February 2013.

- Väyrynen, A. and J. Salminen. 2012. Lithium ion battery production. *The Journal of Chemical Thermodynamics* 46: 80–85.
- Wang, J. and T. Chen. 2012. Surface composition and electrochemical behavior of LiNi<sub>1/3</sub>Co<sub>1/3</sub>Mn<sub>1/3</sub>O<sub>2</sub> cathode material with copper additive. *Rare Metals* 31(4): 397–401.
- Wood, R. and M. Lenzen. 2009. Structural path decomposition. *Energy Economics* 31(3): 335–341. <http://linkinghub.elsevier.com/retrieve/pii/S0140988308001680>. Accessed 26 March 2012.
- World Business Council for Sustainable Development. 2004. *Mobility 2030: Meeting the challenges to sustainability*. London, UK: Seven. [www.wbcsd.org/Pages/EDocument/EDocumentDetails.aspx?ID=69&NoSearchContextKey=true](http://www.wbcsd.org/Pages/EDocument/EDocumentDetails.aspx?ID=69&NoSearchContextKey=true). Accessed 23 October 2012.
- Zackrisson, M., L. Avellan, and J. Orlenius. 2010. Life cycle assessment of lithium-ion batteries for plug-in hybrid electric vehicles—Critical issues. *Journal of Cleaner Production* 18(15): 1519–1529.
- Ziemann, S., M. Weil, and L. Schebek. 2012. Tracing the fate of lithium—The development of a material flow model. *Resources, Conservation and Recycling* 63: 26–34.

## About the Authors

**Linda Ager-Wick Ellingsen** is a researcher at the Industrial Ecology Programme (IndEcol) in the Department of Energy and Process Engineering at the Norwegian University of Science and Technology (NTNU) in Trondheim, Norway. **Guillaume Majeau-Bettez** is a doctoral candidate at IndEcol, NTNU. **Bhawna Singh** is a researcher at IndEcol, NTNU. **Akhilesh Kumar Srivastava** was a research scientist/test and validation manager at Miljøbil Grenland, in Porsgrunn, Norway, at the time the article was written. He is currently a senior scientist at Tel-Tek, Porsgrunn, Norway. **Lars Ole Valøen** was chief technical officer at Miljøbil Grenland at the time the article was written. He is currently chief technical officer at Grenland Energy AS, Porsgrunn, Norway. **Anders Hammer Strømman** is professor at IndEcol, NTNU.

## Supporting Information

Additional supporting information may be found in the online version of this article at the publisher's web site:

**Supporting Information S1:** This supporting information contains a system description and flowcharts, a full inventory of the battery components, complete numerical values of the battery pack, a sensitivity analysis of the number of cycles, and a structural path analysis related to the study presented in the main article.